

# MOPAR STREET ROD REAR AXLES

## CHRYSLER PRODUCTS REAR AXLE INTERCHANGE

YEAR	SERIES	"A" SPRING WIDTH	"B" TRACK WIDTH	"C" RING GEAR DIAMETER
1932-34	All MoPars	43 inches	56 inches	NA
1960-76*	A-Body	43 inches	55.5 inches	7.25 inches
1966-72*	A-Body	43 inches	55.5 inches	8.75 inches
1973-76	A-Body	43 inches	55.5 inches	8.25 inches
1935-36	All MoPars	44 inches	59 inches	NA
1962-70**	B-Body	44 inches	59.2 inches	8.75 inches
1976-80	F-Body	44.46 inches	58.5 inches	8.25 inches
1977-89	M-Body	44.46 inches	58.5 inches	8.25 inches
1980-83	J-Body	44.46 inches	58.5 inches	8.25 inches
1937-48	All MoPars	47 inches	60 inches	NA
1971-74	B-Body	47.3 inches	62.0 inches	8.75 inches
1971-79	B-Body	47.3 inches	62.0 inches	8.25 inches

A-Body	Plymouth Valiant, Duster Dodge Dart, Demon
B-Body	Plymouth Satellite, Belvedere, Road Runner Dodge Coronet, Charger, Super Bee Chrysler Cordoba '75-'79
F-Body	Plymouth Volare Dodge Aspen
M-Body	Dodge Diplomat Chrysler 5th Avenue
J-Body	Dodge Mirada Chrysler Cordoba '80-'83

\* '60-72 A-Body used 5 on 4.0 inch bolt pattern. All other MoPars use 5 on 4.5 inch.

\*\* '62-64 not advised because parking brake was on transmission.